

## Bundle Specifications

## Physical Parameters

Pixel Pitch (mm)	4.0	Resolution (px)	960 x 540
Pixel Configuration	3-in-1 SMD	Cabinet Material	Aluminum
Display Dimensions (W x H, mm)	3,840 x 2,160	Impact Resistant	Yes
Bundle Assembly Weight (kg / lb)	522 / 1,149	Service Access	Front
Mounting System	Factory wall-mounting or flown system		

## Optical Specifications

Brightness (nits)	2,100	Contrast Ratio	10,000:1
Viewing Angle (Horizontal)	160°	Viewing Angle (Vertical)	120°
Colours	281 trillion	Greyscale	16-bit
Refresh Rate (Hz)	4,200		

## Electrical Specifications

Power Consumption (Watts Max.)	3,456	Power Consumption (Watts Avg.)	1,140
Circuits Required (120V / 20A)	2	Power Supply (V)	AC 90-264
Data Runs Required at 8-bit (Standard / Redundant)	1 / 2		

## Operation Specifications

Operating Temperature (°C)	+5°C~+50°C	Operating Humidity	10~90%RH
Lifetime (Hours)	100,000	Standard Warranty	3 Years
BTU/h - Full Bright/Full White	1,915	BTU/h - Full Bright/Average Content	632
BTU/h - 50% Bright/Full White	862	BTU/h - 50% Bright/Average Content	284

## Certification and Compliance

Safety	cETL		
--------	------	--	--

Specifications are subject to change without notice.

Specification report date: 06/01/2024