

Bundle Specifications

Physical Parameters

Pixel Pitch (mm)	4.0	Resolution (px)	1,280 x 720
Pixel Configuration	3-in-1 SMD	Cabinet Material	Aluminum
Display Dimensions (W x H, mm)	5,120 x 2,880	Impact Resistant	Yes
Bundle Assembly Weight (kg / lb)	928 / 2,042	Service Access	Front
Mounting System	Factory wall-mounting or flown system		

Optical Specifications

Brightness (nits)	2,100	Contrast Ratio	10,000:1
Viewing Angle (Horizontal)	160°	Viewing Angle (Vertical)	120°
Colours	281 trillion	Greyscale	16-bit
Refresh Rate (Hz)	4,200		

Electrical Specifications

Power Consumption (Watts Max.)	6,144	Power Consumption (Watts Avg.)	2,028
Circuits Required (120V / 20A)	4	Power Supply (V)	AC 90-264
Data Runs Required at 8-bit (Standard / Redundant)	2 / 4		

Operation Specifications

Operating Temperature (°C)	+5°C~+50°C	Operating Humidity	10~90%RH
Lifetime (Hours)	100,000	Standard Warranty	7 Years
BTU/h - Full Bright/Full White	3,405	BTU/h - Full Bright/Average Content	1,123
BTU/h - 50% Bright/Full White	1,532	BTU/h - 50% Bright/Average Content	506

Certification and Compliance

Safety	cETL
--------	------